



TECHNICAL DATA

MATERIAL:

LLDPE – Linear Low-Density Polyethylene

COLOUR:

Yellow

DETAILS:

Height: 1000 mm
Base diameter: 570 x 520 mm
face diameter: 400 mm

MATERIAL PROPERTIES:

Full UV radiation stabilization
High lightfastness pigments
Good impact resistance
Resistance to chemical agents (petrol, oil, salt)
Suitable for application of reflective foil

WEIGHT:

6 kg

QUANTITY PER PALLET/PACKAGE:

9. / 2

USES:

Intended for marking road obstacles and traffic islands with curbs

PALLET DIMENSIONS:

130x120

 C.D.K. Polska Sp. z o.o. ul. Sikorki 17, 31-589 Kraków	DATA SHEET 2/24/RL	PAGE 2/2
	ROAD BLOCK SIGNS U5B FI 400	02/2024`

PERFORMANCE CHARACTERISTICS OF CONSTRUCTION PRODUCTS AND METHODS FOR THEIR ASSESSMENT

No.	Designation of the construction product type	Essential characteristics of the construction product for the intended use(s)	Performance characteristics expressed in levels, classes or descriptive form	Unit	Test and calculation methods
1.	ROAD BLOCK SIGNS	Tensile strength	≥ 10	Mpa	PN-EN ISO 527
2.		Hardness	≥ 55	°Sh	PN-EN ISO 868
3.		Density	$\geq 0,9$	g/cm ³	PN-EN ISO 1183-1

The road block U5a has:

- National Technical Assessment No. IBDiM-KOT-2017/0090, issue 3,
- National Certificate of Constancy of Performance No. 052-UWB-035/2,
- National Declaration of Performance No. WD-SLU/2023/01.

	CHECKED	APPROVED
	Kontrola Jakości C.D.K. Polska Sp. z o.o.	Marek Malinowski Prezes Zarządu C.D.K. Polska Sp. z o.o.
	Kraków, 02.01.2024	Kraków, 02.01.2024